

# ADAM-4011 ADAM-4012 ADAM-4013

1-ch Thermocouple Input Module

1-ch Analog Input Module

1-ch RTD Input Module



ADAM-4011



ADAM-4012



ADAM-4013



## Specifications

### General

- Power Consumption 1.4 W @ 24 V<sub>DC</sub>
- Supported Protocols ASCII command

### Analog Input

- Channels 1
- Input Impedance Voltage: 2 MΩ  
Current: 125 Ω
- Input Type T/C, mV, V or mA
- Input Range ±15 mV, ±50 mV, ±100 mV,  
±500 mV, ±1 V,  
±2.5 V, ±20 mA
- Accuracy Voltage mode: ±0.1% or  
better  
Current mode: ±0.2% or  
better

### T/C Type and Temperature Range

J	0 ~ 760° C	R	500 ~ 1,750° C
K	0 ~ 1,370° C	S	500 ~ 1,750° C
T	-100 ~ 400° C	B	500 ~ 1,800° C
E	0 ~ 1,000° C		

- Span Drift ±25 ppm/° C
- Zero Drift ±6 μV/° C

### Digital Input

- Channels 1  
Logic level 0: 1 V max.  
Logic level 1: 3.5 ~ 30 V  
Pull up current: 0.5 mA,  
10 kΩ resistor to +5 V
- Event Counter Max. input freq: 50 Hz

### Digital Output

- Channels 2, open collector to 30 V,  
30 mA max. load
- Power Dissipation 300 mW

## Common Specifications

### General

- Power Input Unregulated 10 ~ 30 V<sub>DC</sub>
- Connectors 1 x plug-in terminal block  
(#14 ~ 22 AWG)
- Watchdog Timer System (1.6 second)

### Analog Input

- Resolution 16-bit
- Sampling Rate 10 sample/second

## Specifications

### General

- Power Consumption 1.2 W @ 24 V<sub>DC</sub>
- Supported Protocols ASCII command

### Analog Input

- Channels 1
- Input Impedance Voltage: 20 MΩ  
Current: 125 Ω
- Input Type mV, V or mA
- Input Range ±150 mV, ±500 mV, ±1 V,  
±5 V, ±10 V and ±20 mA
- Accuracy Voltage mode: ±0.1% or  
better  
Current mode: ±0.2% or  
better

- Span Drift ±25 ppm/° C
- Zero Drift ±6 μV/° C

### Digital Input

- Channels 1  
Logic level 0: +1 V max.  
Logic level 1: 3.5 ~ 30 V  
pull up current: 0.5 mA,  
10 kΩ resistor to +5 V  
Max. input freq.: 50 Hz  
Min. input pulse width: 1  
msec.
- Event Counter

### Digital Output

- Channels 2, open collector to 30 V,  
30 mA max. load
- Power Dissipation 300 mW

## Specifications

### General

- Power Consumption 0.7 W @ 24 V<sub>DC</sub>
- Supported Protocols ASCII command

### Analog Input

- Channels 1
- Input Connections 2, 3, or 4-wire
- Input Impedance 2 MΩ
- Input Type Pt or Ni RTD
- RTD Types and Temperature Ranges  
IEC RTD 100 ohms  
Pt -100° C to +100° C a = 0.00385  
Pt 0° C to +100° C a = 0.00385  
Pt 0° C to +200° C a = 0.00385  
Pt 0° C to +600° C a = 0.00385  
JIS RTD 100 ohms  
Pt -100° C to +100° C a = 0.003916  
Pt 0° C to +100° C a = 0.003916  
Pt 0° C to +200° C a = 0.003916  
Pt 0° C to +600° C a = 0.003916

### Ni RTD

- Ni -80° C to +100° C
- Ni 0° C to +100° C
- Accuracy ±0.1% or better
- Span Drift ±25 ppm/° C
- Zero Drift ±3 μV/° C

## Ordering Information

- ADAM-4011 1-ch Thermocouple Input Module
- ADAM-4012 1-ch Analog Input Module
- ADAM-4013 1-ch RTD Input Module